

Mechanical Properties Arminox Stainless Steel Reinforcement

German Zulassung Z-1.4-80 British Standard BS6744:2016

Property	German Standard (Zulassung Z-1.4-80)		British Standard BS 6744		
Grade	1.4571		1.4301, 1.4436 1.4362, 1.4462		
Product	Coil	Bar	Coil, Bar		
0,2 % proof strength - R_{p0,2}	>= 510 N/mm ²	>= 500 N/mm ²	>= 500 N/mm ²		
Ultimate tensile strength - R_m	>= 550 N/mm ²	>= 550 N/mm ²	-		
Stress ratio - R_m / R_{p0,2}	>= 1,08	>= 1,08	>= 1,1		
Total elongation at max. force - A_{gt}	>= 5,5 %	>= 5,0 %	>= 5,0 %		
Elongation at fracture - A₅	-	-	>= 14 %		
Elongation at fracture - A₁₀	>= 16 %	>= 15 %	-		
Bend test	Yes	Yes	Yes		
Cross sectional area	+/- 4 %	+/- 4 %	Nominal		
Ø5	19,6 mm ²	19,6 mm ²	19,6 mm ²		
Ø6	28,3 mm ²	28,3 mm ²	28,3 mm ²		
Ø7	-	-	38,5 mm ²		
Ø8	50,3 mm ²	50,3 mm ²	50,3 mm ²		
Ø10	78,5 mm ²	78,5 mm ²	78,5 mm ²		
Ø12	113,1 mm ²	113,1 mm ²	113,1 mm ²		
Ø14	154,0 mm ²	154,0 mm ²	153,9 mm ²		
Ø16	201,0 mm ²	201,0 mm ²	201,1 mm ²		
Ø20	-	-	314,2 mm ²		
Ø25	-	-	490,9 mm ²		
Ø32	-	-	804,2 mm ²		
Ø40	-	-	1256,6 mm ²		
Ø50	-	-	1963,5 mm ²		
Nominal weight per meter run	-	-	Tolerance		
			Ø5 - Ø6	+/- 9 %	
			Ø7 - Ø12	+/- 6 %	
			>Ø12	+/- 4,5 %	
			1.4301	1.4436	1.4362, 1.4462
Ø5	0,156 kg	0,156 kg	0,155 kg	0,157 kg	0,153 kg
Ø6	0,226 kg	0,226 kg	0,224 kg	0,226 kg	0,221 kg
Ø7	-	-	0,304 kg	0,308 kg	0,300 kg
Ø8	0,401 kg	0,401 kg	0,397 kg	0,402 kg	0,392 kg
Ø10	0,626 kg	0,626 kg	0,620 kg	0,628 kg	0,612 kg



Property	German Standard (Zulassung Z-1.4-80)		British Standard BS 6744		
			Tolerance		
Nominal weight per meter run	-	-	Ø5 - Ø6	+/- 9,0%	
			Ø7 - Ø12	+/- 6,0%	
	Coil	Bar	>Ø12	+/- 4,5%	
	1.4571	1.4571	1.4301	1.4436	1.4362, 1.4462
Ø12	0,903 kg	0,903 kg	0,893 kg	0,905 kg	0,882 kg
Ø14	1,229 kg	1,229 kg	1,216 kg	1,231 kg	1,200 kg
Ø16 – without Zulassung	1,604 kg	1,604 kg	1,589 kg	1,609 kg	1,569 kg
Ø20	-	-	2,482 kg	2,514 kg	2,451 kg
Ø25	-	-	3,878 kg	3,927 kg	3,829 kg
Ø32	-	-	6,353 kg	6,434 kg	6,266 kg
Ø40	-	-	9,927 kg	10,053 kg	9,790 kg
Ø50	-	-	15,512 kg	15,708 kg	15,297 kg
Relative rib area f_r	Coil	Bar	Coil, Bar		
	1.4571	1.4571	1.4301	1.4436	1.4362, 1.4462
Nominal size	Min.	Min.	Min.		
Ø5	0,04485	0,039	0,039		
Ø6	0,04485	0,039	0,039		
Ø7	-	-	0,045		
Ø8	0,05175	0,045	0,045		
Ø10	0,05980	0,052	0,052		
Ø12	0,06444	0,056	0,056		
Ø14	0,06444	0,056	0,056		
Ø16	0,06444	0,056	0,056		
Ø20	-	-	0,056		
Ø25	-	-	0,056		
Ø32	-	-	0,056		
Ø40	-	-	0,056		
Ø50	-	-	0,056		

